



## Safety Data Sheet

### Illuminating Paraffin

Version 1.02

Revision Date 11.01.2011

---

#### 1. Identification of the substance/mixture and of the company/undertaking

<b>Trade name</b>	<b>Illuminating Paraffin</b>
<b>Synonyms</b>	<b>Illuminating Paraffin, Lamp Oil, Illuminating Kerosine</b>
<b>Company</b>	Sasol Oil 32 Hill Street Randburg, 2125 South Africa
<b>Information (Product safety)</b>	<b>Telephone:</b> +27 11 889 7600 <b>Fax:</b> <b>E-mail address</b> <a href="mailto:msds.info@sasol.com">msds.info@sasol.com</a>
<b>Emergency telephone</b>	Europe, Israel, Africa, Americas +44 (0)1235 239 670 Middle East, Arabic African countries +44 (0)1235 239 671 Asia Pacific +65 3158 1074 China +86 10 5100 3039 South Africa +27 (0)17 610 4444 Australia +61 2 9032 0460

---

#### 2. Hazards identification

##### Identification of the risks

R45	May cause cancer.
R65	Also harmful: may cause lung damage if swallowed.
R10	Flammable.
R38	Irritating to skin.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R67	Vapours may cause drowsiness and dizziness.

##### Particular risks to human beings and the environment

Very toxic to aquatic organisms.

---

#### 3. Composition/information on ingredients

##### Preparation on the base:

**Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha**

**Contents:** >= 60.00 %W/W

**CAS-No.** 64742-82-1

**Index-No.** 649-330-00-2

**EC-No.** 265-185-4



## Safety Data Sheet

### Illuminating Paraffin

Version 1.02

Revision Date 11.01.2011

**Symbol(s)** T **R-phrases** -R45 -R46 -R65

**Kerosine (petroleum); Straight run kerosine**

**Contents:** <= 20.00 %W/W

**CAS-No.** 8008-20-6

**Index-No.** 649-404-00-4

**EC-No.** 232-366-4

**Symbol(s)** Xn

**R-phrases** -R65

**heptane; n-heptane**

**Contents:** >= 5.00 - <= 10.00 %W/W

**CAS-No.** 142-82-5

**Index-No.** 601-008-00-2

**EC-No.** 205-563-8

**Symbol(s)** F, Xn, N

**R-phrases** -R11 -R38 -R50/53 -R65 -R67

**octane; n-octane**

**Contents:** <= 10.00 %W/W

**CAS-No.** 111-65-9

**Index-No.** 601-009-00-8

**EC-No.** 203-892-1

**Symbol(s)** F, Xn, N

**R-phrases** -R11 -R38 -R50/53 -R65 -R67

**methylcyclohexane**

**Contents:** >= 5.00 - <= 10.00 %W/W

**CAS-No.** 108-87-2

**Index-No.** 601-018-00-7

**EC-No.** 203-624-3

**Symbol(s)** F, Xn, N

**R-phrases** -R11 -R38 -R65 -R67 -R51/53

**cyclohexane**

**Contents:** >= 1.00 - <= 5.00 %W/W

**CAS-No.** 110-82-7

**Index-No.** 601-017-00-1

**EC-No.** 203-806-2

**Symbol(s)** F, Xn, N

**R-phrases** -R11 -R38 -R65 -R67 -R50/53

**toluene**

**Contents:** >= 1.00 - <= 5.00 %W/W

**CAS-No.** 108-88-3

**Index-No.** 601-021-00-3

**EC-No.** 203-625-9

**Symbol(s)** F, Xn

**R-phrases** -R11 -R38 -R48/20 -R63 -R65 -R67

**xylene**

**Contents:** >= 1.00 - <= 5.00 %W/W

**CAS-No.** 1330-20-7

**Index-No.** 601-022-00-9

**EC-No.** 215-535-7



## Safety Data Sheet

### Illuminating Paraffin

Version 1.02

Revision Date 11.01.2011

**Symbol(s) Xn** **R-phrase(s)** -R10 -R20/21 -R38

For the full text of the R-phrases mentioned in this Section, see Section 16.

#### 4. First aid measures

<b>General advice</b>	Immediate medical attention is required.
<b>Inhalation</b>	Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.
<b>Skin contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Call a physician immediately.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Call a physician immediately.
<b>Ingestion</b>	If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water spray, Dry powder, Foam
<b>Specific hazards during fire fighting</b>	Flash back possible over considerable distance.
<b>Special protective equipment for fire-fighters</b>	Wear self-contained breathing apparatus and protective suit.
<b>Further information</b>	Cool containers / tanks with water spray.

#### 6. Accidental release measures

<b>Personal precautions</b>	Keep people away from and upwind of spill/leak. Remove all sources of ignition. Do not breathe vapours or spray mist.
<b>Environmental precautions</b>	Should not be released into the environment. Prevent further leakage or spillage if safe to do so.
<b>Methods for cleaning up</b>	Soak up with inert absorbent material and dispose of as hazardous waste.

#### 7. Handling and storage

**Handling**



## Safety Data Sheet

### ILLUMINATING PARAFFIN

Version 1.02

Revision Date 11.01.2011

**Safe handling advice** Provide sufficient air exchange and/or exhaust in work rooms.  
Wear personal protective equipment.

**Advice on protection against fire and explosion** Keep away from heat and sources of ignition. Use explosion-proof equipment.

#### Storage

**Requirements for storage areas and containers** Keep containers tightly closed in a dry, cool and well-ventilated place.

## 8. Exposure controls/personal protection

#### Components with workplace control parameters

##### NATIONAL OCCUPATIONAL EXPOSURE LIMITS

##### EUROPEAN OCCUPATIONAL EXPOSURE LIMITS

Components	Type	Control parameters	Update	Basis
N-HEPTANE	TWA	2,085 mg/m <sup>3</sup>	12 2009	EU Exposure Limit Values
	TWA	500 ppm	12 2009	EU Exposure Limit Values
XYLENE, MIXED ISOMERS, PURE	TWA	221 mg/m <sup>3</sup>	12 2009	EU Exposure Limit Values
	TWA	50 ppm	12 2009	EU Exposure Limit Values
	STEL	442 mg/m <sup>3</sup>	12 2009	EU Exposure Limit Values
	STEL	100 ppm	12 2009	EU Exposure Limit Values

#### Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

#### Personal protective equipment

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Hand protection** Gloves suitable for permanent contact:  
Material: butyl-rubber  
Break through time: 4 h  
Material thickness: 0.5 mm  
unsuitable gloves  
Material: Polyvinylchloride, leather, nitrile rubber/nitrile latex, natural rubber/natural latex

**Eye protection** Safety glasses with side-shields



## Safety Data Sheet

### illuminating Paraffin

Version 1.02

Revision Date 11.01.2011

<b>Skin and body protection</b>	Protective suit, Safety shoes
<b>Hygiene measures</b>	Wash hands before breaks and immediately after handling the product.
<b>Protective measures</b>	Wear suitable protective equipment.

### 9. Physical and chemical properties

<b>Form</b>	liquid
<b>state of matter</b>	liquid; at 20 °C; 1,013 hPa
<b>Colour</b>	Clear to light yellowish brown
<b>Odour</b>	Hydrocarbon-like petroleum
<b>Pour point</b>	0 °C
<b>Boiling point/boiling range</b>	160 °C
<b>Flash point</b>	45 °C
<b>Density</b>	0.77 g/cm <sup>3</sup> ; 20 °C
<b>Water solubility</b>	Insoluble
<b>Viscosity, kinematic</b>	3 mm <sup>2</sup> /s; 50 °C

### 10. Stability and reactivity

<b>Materials to avoid</b>	Oxidizing agents, Reducing agents
---------------------------	-----------------------------------

### 11. Toxicological information

<b>Acute oral toxicity</b>	Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha: LD50 rat: > 5,000 mg/kg; (literature value)  Kerosine (petroleum); Straight run kerosine: LD50 rat: > 5,000 mg/kg; (literature value)  toluene: LD50 rat: 5,000 mg/kg; literature value
<b>Acute inhalation toxicity</b>	Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha: LC50 rat: > 12 mg/l; ; 6 h(literature value)  Kerosine (petroleum); Straight run kerosine: LC50 rat: > 5 mg/l; ; 4 h(literature value)  toluene: LC50 mouse: 5,320 mg/l; literature value



## Safety Data Sheet

### illuminating Paraffin

Version 1.02

Revision Date 11.01.2011

<b>Acute dermal toxicity</b>	Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha: LD50 rabbit: > 2,000 mg/kg; (literature value)  Kerosine (petroleum); Straight run kerosine: LD50 rabbit: > 2,000 mg/kg; (literature value)  toluene: LD50 rat: 12,124 mg/kg; literature value
<b>Skin irritation</b>	toluene: rabbit: moderately irritating; (literature value)
<b>Eye irritation</b>	Kerosine (petroleum); Straight run kerosine: rabbit: not irritating; Draize Test; (literature value)  toluene: rabbit: Mild eye irritation; (literature value)
<b>Sensitisation</b>	Kerosine (petroleum); Straight run kerosine: Buehler Test guinea pig: ; Did not cause sensitization on laboratory animals.

## 12. Ecological information

### Ecotoxicity effects

<b>Toxicity to fish</b>	toluene: LC50 Pimephales promelas: 34.27 mg/l; 96 h; literature value  toluene: LC50 Poecilia reticulata: 59.3 mg/l; 96 h; literature value  toluene: LC50 Cyprinodon variegatus: 277 mg/l; 96 h; literature value
<b>Toxicity to daphnia and other aquatic invertebrates.</b>	toluene: LC50 Daphnia magna: 313 mg/l; 48 h; literature value

## 13. Disposal considerations

<b>Product</b>	Dispose of as special waste in compliance with local and national regulations.
<b>Contaminated packaging</b>	Contaminated packaging should be emptied optimally and after being suitably cleaned returned for re-use., Store containers and offer for recycling of material when in accordance with the local regulations.

## 14. Transport information

<b>ADR</b>	UN-Number: 1223; Class: 3; Packaging group: III; F1; Description of the goods: KEROSENE
------------	--



## Safety Data Sheet

### Illuminating Paraffin

Version 1.02

Revision Date 11.01.2011

<b>RID</b>	UN-Number: 1223; Class: 3; Packaging group: III; F1; Description of the goods: KEROSENE
<b>ADNR</b>	UN-Number: 1223; Class: 3; Packaging group: III; F1; Description of the goods: KEROSENE
<b>IMDG</b>	UN-Number: 1223; Class: 3; EmS: F-E, S-E; Packaging group: III; Description of the goods: KEROSENE
<b>ICAO/IATA</b>	UN-Number : 1223; Class: 3; Packaging group: III; Description of the goods: Kerosene

## 15. Regulatory information

### Labelling



<b>Regulatory base</b>	1999/45/EC
<b>Symbol(s)</b>	T: Toxic N: Dangerous for the environment
<b>R-phrase(s)</b>	R45: May cause cancer. R65: Also harmful: may cause lung damage if swallowed. R10: Flammable. R38: Irritating to skin. R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R63: Possible risk of harm to the unborn child. R67: Vapours may cause drowsiness and dizziness.
<b>S-phrase(s)</b>	S53: Avoid exposure - obtain special instructions before use. S35: This material and its container must be disposed of in a safe way. S36/37: Wear suitable protective clothing and gloves. S43: In case of fire, use sand, dry chemical or alcohol-resistant foam. S61: Avoid release to the environment. Refer to special instructions/ Safety data sheets.



## Safety Data Sheet

### Illuminating Paraffin

Version 1.02

Revision Date 11.01.2011

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**Special labelling of certain mixtures**

Restricted to professional users.

**Hazardous components which must be listed on the label**

Naphtha (petroleum), hydrodesulfurized heavy; Low boiling point hydrogen treated naphtha

toluene

## 16. Other information

*Full text of R-phrases referred to under sections 2 and 3*

R10	Flammable.
R11	Highly flammable.
R20/21	Harmful by inhalation and in contact with skin.
R38	Irritating to skin.
R45	May cause cancer.
R46	May cause heritable genetic damage.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R67	Vapours may cause drowsiness and dizziness.

All reasonable efforts were exercised to compile this SDS in accordance with ISO 11014 and ANSIZ400.1.1993. The MSDS provides information regarding the health, safety and environmental hazards, at the date of issue, to facilitate the safe receipt, use and handling of the product in the workplace. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which the product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which the product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place as regards health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may be involved in the receipt, use or handling of the product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy or assume any liability for the incompleteness of the information contained herein or any advice given. The product is sold and risk passes in accordance with the specific terms and conditions of sale.

The MSDS was created by: MOTLATSI  
The MSDS was approved by: S. Shabalala





**Safety Data Sheet**

***Illuminating Paraffin***

*Version 1.02*

*Revision Date 11.01.2011*

---